

### Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

#### Listing of Claims:

1. (currently amended) A rotary press comprising:
  - a first cylinder having a pair of cylinder segments which can be rotated independently of each other;
  - a pair of electric motors connected to respective said cylinder segments by respective drive connections so that said cylinder segments can be driven independently of one another;
  - a second cylinder; ~~and~~
  - a dedicated electric motor which drives said second cylinder synchronously with said first cylinder, the dedicated electric motor driving only said second cylinder; and  
means for limiting rotation of at least one of said cylinders and said cylinder segments relative to a desired position, said means for limiting rotation comprising rotation-limiting spur gears fixed to at least one of said cylinders and said cylinder segments, said rotation-limiting spur gears each having teeth with tooth flanks, said rotation-limiting spur gears meshing with rotational flank play and without said tooth flanks touching one another.
2. (currently amended) A rotary press as in claim 1 further comprising:
  - a further cylinder;
  - a first spur gear fixed to said further cylinder
  - a second spur gear fixed to one of said cylinder segments of said first cylinder and having a drive connection to said first spur gear fixed to said further cylinder.
3. (previously presented) A rotary press as in claim 1 further comprising:
  - a further cylinder which rotates synchronously with said first cylinder, said further cylinder having a pair of cylinder segments which can be rotated independently of each other; and

a pair of electric motors connected to respective said cylinder segments of said further cylinder by respective drive connections so that said cylinder segments of said further cylinder can be driven independently of one another, at least one of said pair of electric motors driving only one of said cylinder segments of said further cylinder.

4. (withdrawn) A rotary press as in claim 1, wherein the first cylinder is a folding cylinder and said pair of cylinder segments comprise first and second cylinder segments which can be rotated independently of each other, said first cylinder segment bearing holding elements, said second cylinder bearing folding blades, and wherein said second cylinder is a folding jaw cylinder.

5. (withdrawn - previously presented) A rotary press as in claim 4 wherein said folding jaw cylinder comprises first and second cylinder segments which each bear folding jaws and can rotate relative to each other, each of said cylinder segments of said folding jaw cylinder being driven by a respective said dedicated electric motor so that said cylinder segments of said folding jaw cylinder can be driven independently of one another, said press further comprising:

a gripper folding blade cylinder comprising a first cylinder segment bearing grippers and a second cylinder segment bearing folding blades; and

a pair of electric motors connected to respective said cylinder segments of said gripper folding blade cylinder by respective drive connections so that said cylinder segments of said gripper folding blade cylinder can be driven independently of one another, at least one of said pair of electric motors driving only one of said cylinder segments of said gripper folding blade cylinder.

6. (withdrawn - currently amended) A rotary press as in claim 4 further comprising:

a knife cylinder;

a first spur gear fixed to said knife cylinder;

a second spur gear fixed to one of said cylinder segments of said folding cylinder and having a drive connection to said first spur gear fixed to said ~~further~~ knife cylinder; and

a pinion connected to said electric motor driving said first segment of said folding cylinder, said pinion engaging one of said first and second spur gears.

7. (withdrawn) A rotary press as in claim 4 further comprising:  
a knife cylinder; and  
an electric motor which drives said knife cylinder synchronously with said folding cylinder.

8. (withdrawn) A rotary press as in claim 4 further comprising a motor control system for presetting the angular positions of the driven cylinders, said motor control system comprising a computing and storage unit in which said angular positions are stored, said computing and storage unit having an input side connected to said electric motors.

9.-10. (canceled)

11. (withdrawn) A rotary press as in claim 4 wherein said cylinder segments of each said cylinder having segments comprise stops which limit relative rotation of said cylinder segments.

12. (withdrawn) A rotary press as in claim 4 wherein said cylinder segments of each said cylinder having segments comprise hardware limit switches which limit relative rotation of said cylinder segments.

13. (withdrawn) A rotary press as in claim 4 further comprising a position control system for said electric motors, said position control system containing desired limiting values for limiting the mutual rotatability of the cylinder segments and the cylinders.

14. (withdrawn) A rotary press as in claim 4 wherein at least one of said electric motors is configured as a torque motor.

15. (original) A rotary press as in claim 1 further comprising a motor control system for presetting the angular positions of the driven cylinders, said motor control system comprising a computing and storage unit in which said angular positions are stored, said computing and storage unit having an input side connected to said electric motors.

16.-17. (canceled)

18. (original) A rotary press as in claim 1 wherein said cylinder segments of each said cylinder having segments comprise stops which limit relative rotation of said cylinder segments.

19. (original) A rotary press as in claim 1 wherein said cylinder segments of each said cylinder having segments comprise hardware limit switches which limit relative rotation of said cylinder segments.

20. (original) A rotary press as in claim 1 further comprising a position control system for said electric motors, said position control system containing desired limiting values for limiting the mutual rotatability of the cylinder segments and the cylinders.